

UK CA	
Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO)	
22 001MRZUK	
EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$, for internal and external walls and floorings	
Reaction to fire	Class A1 _{FL} /A1
Breaking strength	Thickness <7,5 mm Breaking strength ≥ 700 N Thickness $\geq 7,5$ mm Breaking strength ≥ 1300 N
Durability, for: - Internal use - External use: Freeze/thaw resistance	Passed Passed
Resistance to thermal shock	Passed



**Marazzi Group s.r.l. a socio unico,
Viale Regina Pacis 39
41049 Sassuolo (MO)**

22

002MRZUK

EN 14411:2012

**Dry-pressed ceramic tiles, with water absorption $0,5\% < E_b \leq 3\%$,
for internal and external walls and floorings**

Reaction to fire	Class A1 _{FL} /A1
Breaking strength	Thickness <7,5 mm Breaking strength ≥ 700 N Thickness $\geq 7,5$ mm Breaking strength ≥ 1100 N
Durability, for: - Internal use - External use: Freeze/thaw resistance	Passed Passed
Resistance to thermal shock	Passed



**Marazzi Group s.r.l. a socio unico,
Viale Regina Pacis 39
41049 Sassuolo (MO)**

22

003MRZUK

EN 14411:2012

**Dry-pressed ceramic tiles, with water absorption $3% < E_b \leq 6%$,
for internal walls and floorings**

Reaction to fire	Class A1 _{FL} /A1
Breaking strength	Thickness <7,5 mm Breaking strength ≥ 600 N Thickness $\geq 7,5$ mm Breaking strength ≥ 1000 N
Durability, for: -Internal use	Passed



**Marazzi Group s.r.l. a socio unico,
Viale Regina Pacis 39
41049 Sassuolo (MO)**

22

004MRZUK

EN 14411:2012

**Dry-pressed ceramic tiles, with water absorption $6% < E_b \leq 10%$,
for internal walls**

Reaction to fire	Class A1
Durability, for: - Internal use	Passed



**Marazzi Group s.r.l. a socio unico,
Viale Regina Pacis 39
41049 Sassuolo (MO)**

22

005MRZUK

EN 14411:2012

**Dry-pressed ceramic tiles, with water absorption $E_b > 10%$,
for internal walls**

Reaction to fire	Class A1
Durability, for: - Internal use	Passed



**Marazzi Group s.r.l. a socio unico,
Viale Regina Pacis 39
41049 Sassuolo (MO)**

05

006MRZUK

EN 14411:2012

**Dry-pressed ceramic tiles, with water absorption $3% < E_b \leq 6%$,
for internal walls**

Reaction to fire	Class A1
Durability, for: - Internal use	Passed



**Marazzi Group s.r.l. a socio unico,
Viale Regina Pacis 39
41049 Sassuolo (MO)**

22

007MRZUK

EN 14411:2012

**Dry-pressed ceramic tiles, with water absorption $E_b > 10%$,
for internal walls and floorings**

Reaction to fire	Class A1 _{FL} /A1
Breaking strength	Thickness <7,5 mm Breaking strength ≥ 200 N Thickness $\geq 7,5$ mm Breaking strength ≥ 600 N
Durability, for: - Internal use	Passed



Marazzi Group s.r.l. a socio unico,
Viale Regina Pacis 39
41049 Sassuolo (MO)

22

009MRZUK

EN 14411:2012

Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$,
for internal and external walls

Reaction to fire	Class A1
Durability, for: - Internal use - External use: Freeze/thaw resistance	Passed Passed
Resistance to thermal shock	Passed

Rev.0



Marazzi Group s.r.l. a socio unico,
Viale Regina Pacis 39
41049 Sassuolo (MO)

22

010MRZUK

EN 14411:2012

Dry-pressed ceramic tiles, with water absorption $0,5\% < E_b \leq 3\%$,
for internal and external walls

Reaction to fire	Class A1
Durability, for: - Internal use - External use: Freeze/thaw resistance	Passed Passed
Resistance to thermal shock	Passed



**Marazzi Group s.r.l. a socio unico,
Viale Regina Pacis 39
41049 Sassuolo (MO)**

22

011MRZUK

EN 14411:2012

**Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$,
for internal walls**

Reaction to fire	Class A1
Durability, for: - Internal use	Passed
Resistance to thermal shock	Passed